

## Determination of accuracy contour and optimization of workpiece positioning for robot milling

Gotlih, J.<sup>a,\*</sup>, Brezocnik, M.<sup>a</sup>, Balic, J.<sup>a</sup>, Karner, T.<sup>a</sup>, Razborssek, B.<sup>a</sup>, Gotlih, K.<sup>a</sup>

<sup>a</sup>Faculty of mechanical engineering, University of Maribor, Maribor, Slovenia

### ABSTRACT

Workpiece positioning into a machine's workspace has become a simple task. Advanced CNC machines are equipped with standardized clamping systems, allowed workpiece dimensions are listed in the machine's documentation and tolerance levels of the end produced parts are known. This gives users plenty of information and good confidence that they are choosing the best machine for a specific task. For more universal machines like industrial robots this is not the case. Due to their flexibility industrial robots can be an alternative to specialized CNC machines, but when a specific task should be executed, important information is missing. For a standard industrial robot the mechanisms layout, its dimensions and its reachable workspace is known, but accuracy levels over the robot's workspace are not. If a workpiece should be milled within certain accuracy limits the robot's documentation offers no information on how close it can be located to the borders of the robot's workspace. This article deals with the mentioned problem with a novel methodology. Based on experimental data we found that a standard 6 DOF industrial robot's reachable workspace can be divided into two regions, one with suitable milling accuracy and another with rapidly decreasing milling accuracy. To isolate the suitable accuracy region a regional non-dominated sorting algorithm was developed and an accuracy contour separating the regions was extracted. In the second part of the article a genetic search algorithm based on regional non-dominated sorting was applied to find the biggest arbitrary shaped workpiece's size, position and orientation in the suitable milling accuracy region of the robot's workspace.

© 2017 PEI, University of Maribor. All rights reserved.

### ARTICLE INFO

**Keywords:**  
Robot milling  
Accuracy contours  
Workpiece positioning  
Non-dominated sorting  
Genetic algorithm  
Optimization

**\*Corresponding author:**  
[janez.gotlih@um.si](mailto:janez.gotlih@um.si)  
(Gotlih, J.)

**Article history:**  
Received 26 May 2017  
Revised 20 July 2017  
Accepted 24 July 2017

### References

- [1] Kubela, T., Pochyly, A., Singule, V. (2016). Assessment of industrial robots accuracy in relation to accuracy improvement in machining processes, In: *2016 IEEE International Power Electronics and Motion Control Conference (PEMC)*, Varna, Bulgaria, 720-725, doi: [10.1109/EPEPEMC.2016.7752083](https://doi.org/10.1109/EPEPEMC.2016.7752083).
- [2] Wu, Y., Klimchik, A., Caro, S., Furet, B., Pashkevich, A. (2015). Geometric calibration of industrial robots using enhanced partial pose measurements and design of experiments, *Robotics and Computer-Integrated Manufacturing*, Vol. 35, 151-168, doi: [10.1016/j.rcim.2015.03.007](https://doi.org/10.1016/j.rcim.2015.03.007).
- [3] Józwick, J., Ostrowski, D., Jarosz, P., Mika, D. (2016). Industrial robot repeatability testing with high speed camera Phantom V2511, *Advances in Science and Technology Research Journal*, Vol. 10, No. 32, 86-96, doi: [10.12913/22998624/65136](https://doi.org/10.12913/22998624/65136).
- [4] Marônek, M., Bárta, J., Ertel, J. (2015). Inaccuracies of industrial robot positioning and methods of their correction, *Tehnički vjesnik – Technical Gazette*, Vol. 22, No. 5, 1207-1212, doi: [10.17559/TV-20140416123902](https://doi.org/10.17559/TV-20140416123902).
- [5] Jezeršek, M., Kos, M., Kosler, H., Možina, J. (2017). Automatic teaching of a robotic remote laser 3D processing system based on an integrated laser-triangulation profilometry, *Tehnički vjesnik – Technical Gazette*, Vol. 24, No. 1, 89-95, doi: [10.17559/TV-20160504230058](https://doi.org/10.17559/TV-20160504230058).

- [6] Papa, G., Torkar, D. (2009), Visual control of an industrial robot manipulator: Accuracy estimation, *Strojniški vestnik – Journal of Mechanical Engineering*, Vol. 55, No. 12, 781-787.
- [7] Yoshikawa, T. (1985). Manipulability of robotic mechanisms, *The International Journal of Robotics Research*, Vol. 4, No. 2, 3-9, doi: [10.1177/027836498500400201](https://doi.org/10.1177/027836498500400201).
- [8] Gotlih, K., Kovac, D., Vuherer, T., Brezovnik, S., Brezocnik, M., Zver, A. (2011). Velocity anisotropy of an industrial robot, *Robotics and Computer-Integrated Manufacturing*, Vol. 27, No. 1, 205-211, doi: [10.1016/j.rcim.2010.07.010](https://doi.org/10.1016/j.rcim.2010.07.010).
- [9] Merlet, J.P. (2005). Jacobian, manipulability, condition number, and accuracy of parallel robots, *Journal of Mechanical Design*, Vol. 128, No. 1, 199-206, doi: [10.1115/1.2121740](https://doi.org/10.1115/1.2121740).
- [10] Mansouri, I., Ouali, M. (2011). The power manipulability – A new homogeneous performance index of robot manipulators, *Robotics and Computer-Integrated Manufacturing*, Vol. 27, No. 2, 434-449, doi: [10.1016/j.rcim.2010.09.004](https://doi.org/10.1016/j.rcim.2010.09.004).
- [11] Vosniakos, G.-C., Matsas, E. (2010). Improving feasibility of robotic milling through robot placement optimisation, *Robotics and Computer-Integrated Manufacturing*, Vol. 26, No. 5, 517-525, doi: [10.1016/j.rcim.2010.04.001](https://doi.org/10.1016/j.rcim.2010.04.001).
- [12] Aly, M.F., Abbas, A.T. (2014). Simulation of obstacles' effect on industrial robots' working space using genetic algorithm, *Journal of King Saud University – Engineering Sciences*, Vol. 26, No. 2, 132-143, doi: [10.1016/j.jksues.2012.12.005](https://doi.org/10.1016/j.jksues.2012.12.005).
- [13] dos Santos, R.R., Steffen, V. Jr., Saramago, S.F.P. (2008). Robot path planning in a constrained workspace by using optimal control techniques, *Multibody System Dynamics*, Vol. 19, No. 1-2, 159-177, doi: [10.1007/s11044-007-9059-1](https://doi.org/10.1007/s11044-007-9059-1).
- [14] Dolgui, A., Pashkevich, A. (2009). Manipulator motion planning for high-speed robotic laser cutting, *International Journal of Production Research*, Vol. 47, No. 20, 5691-5715, doi: [10.1080/00207540802070967](https://doi.org/10.1080/00207540802070967).
- [15] Lin, Y., Zhao, H., Ding, H. (2017). Posture optimization methodology of 6R industrial robots for machining using performance evaluation indexes, *Robotics and Computer-Integrated Manufacturing*, Vol. 48, 59-72, doi: [10.1016/j.rcim.2017.02.002](https://doi.org/10.1016/j.rcim.2017.02.002).
- [16] Kuss, A., Drust, M., Verl, A. (2016). Detection of workpiece shape deviations for tool path adaptation in robotic deburring systems, *Procedia CIRP*, Vol. 57, 545-550, doi: [10.1016/j.procir.2016.11.094](https://doi.org/10.1016/j.procir.2016.11.094).
- [17] Klancnik, S., Brezovnik, S., Brezocnik, M., Balic, J., Ficko, M., Pahole, I., Buchmeister, B. (2009). Advanced concept of milling with robot, *Scientific Bulletin Series C: Fascicle Mechanics, Tribology, Machine Manufacturing Technology*, Vol. 23, No. 100, 73-78.
- [18] Karimi, D., Nategh, M.J. (2016). Contour maps for developing optimal toolpath and workpiece setup in hexapod machine tools by considering the kinematics nonlinearity, *Proceedings of the Institution of Mechanical Engineers, Part B: Journal of Engineering Manufacture*, Vol. 230, No. 9, 1572-1583, doi: [10.1177/0954405415592123](https://doi.org/10.1177/0954405415592123).
- [19] Wei, H., Tang, X.-S., Liu, H. (2015). A genetic algorithm(GA)-based method for the combinatorial optimization in contour formation, *Applied Intelligence*, Vol. 43, No. 1, 112-131, doi: [10.1007/s10489-014-0633-y](https://doi.org/10.1007/s10489-014-0633-y).
- [20] Truong-Hong, L., Laefer, D.F. (2014). Octree-based, automatic building façade generation from LiDAR data, *Computer-Aided Design*, Vol. 53, 46-61, doi: [10.1016/j.cad.2014.03.001](https://doi.org/10.1016/j.cad.2014.03.001).
- [21] Awrangjeb, M., Lu, G. (2015). A triangulation-based technique for building boundary identification from point cloud data, In: *2015 International Conference on Image and Vision Computing New Zealand (IVCNZ)*, Auckland, New Zealand, 1-6, doi: [10.1109/IVCNZ.2015.7761536](https://doi.org/10.1109/IVCNZ.2015.7761536).
- [22] Veber, M. (2016). *Manipulability analysis of milling robot Kuka KR 150-2*, Master thesis, Faculty of Electrical Engineering and Computer Science, University of Maribor, Maribor, Slovenia.

## Določitev meje natančnosti in optimizacija postavitve obdelovanca pri robotskem rezkanju

Gotlih, J.<sup>a,\*</sup>, Brezocnik, M.<sup>a</sup>, Balic, J.<sup>a</sup>, Karner, T.<sup>a</sup>, Razborsek, B.<sup>a</sup>, Gotlih, K.<sup>a</sup>

<sup>a</sup>Faculty of mechanical engineering, University of Maribor, Maribor, Slovenia

### POVZETEK

Postavitev obdelovanca v delovni prostor obdelovalnega stroja je dandanes preprosta naloga. Sodobni CNC stroji so opremljeni s standardiziranimi vpenjalnimi napravami, dovoljene mere obdelovanca so predpisane v dokumentaciji stroja, tolerančne mere končnega izdelka pa so znane vnaprej. Uporabnik tako brez težav izbere najboljši stroj za določeno nalogo. Za bolj splošne naprave kot so industrijski roboti pa to ne velja. Zaradi svoje prilagodljivosti so industrijski roboti lahko alternativa specializiranim CNC strojem, a ko je potrebno izvesti določeno nalogo, pomembni podatki manjkajo. Za standardne industrijske robote proizvajalec podaja topologijo, mere in dosegljiv delovni prostor, natančnosti po celotnem delovnem prostoru pa ne. Če želimo rezkati izdelek z določeno natančnostjo, v dokumentaciji ne najdemo podatka kako blizu mej delovnega prostora robota se obdelovanec še lahko nahaja. Ta prispevek predlaga novo metodologijo za rešitev omenjenega problema. Na podlagi eksperimentalnih podatkov je bilo ugotovljeno, da lahko delovni prostor industrijskega robota s šestimi prostostnimi stopnjami razdelimo na dve področji, eno s primerno natančnostjo rezkanja in eno s hitro padajočo natančnostjo rezkanja. Za osamitev področja primerne za rezkanje smo razvili algoritem za področno nedominirano razvrščanje in pridobili mejo natančnosti, ki ločuje omenjeni področji. V drugi polovici prispevka smo uporabili genetski algoritem zasnovan na nedominiranem razvrščanju in našli največji obdelovanec poljubne oblike ter njegovo pozicijo in orientacijo v področju primerne za rezkanje znotraj celotnega delovnega prostora robota.

© 2017 PEI, University of Maribor. All rights reserved.

### PODATKI O ČLANKU

#### *Ključne besede:*

Robotsko rezkanje  
Meja natančnosti  
Postavitev obdelovanca  
Nedominirano razvrščanje  
Genetski algoritem  
Optimizacija

#### *\*Kontaktna oseba:*

janez.gotlih@um.si  
(Gotlih, J.)

#### *Zgodovina članka:*

Prejet 26. maja 2016  
Popravljen 20. julija 2016  
Sprejet 24. julija 2016