

# Experimental and numerical investigation of the deep drawing process using a tractrix die – An industrial case study focused on stress and temperature analysis

Mandic, V.<sup>a,\*</sup>, Milosavljevic, Dj.<sup>b</sup>, Jurkovic, Z.<sup>c</sup>, Adamovic, D.<sup>a</sup>

<sup>a</sup>Faculty of Engineering of the University of Kragujevac, Kragujevac, Serbia

<sup>b</sup>Sloboda a.d., Cacak, Serbia

<sup>c</sup>Faculty of Engineering of the University of Rijeka, Rijeka, Croatia

## ABSTRACT

The deep drawing process of thick sheet metal for vessel production is carried out by applying a tractrix die with the absence of a blank holder, which has economic benefits for industrial production. The main aim of the paper is the development of a reliable numerical thermo-mechanical model of a silicon brass vessel manufactured by a deep drawing process in a tractrix die and a subsequent ironing process, which includes the previous assembly of the dies with reinforcing rings that creates the required prestresses. The testing of the mechanical properties of silicon brass CuZn24Si was carried out by a standard uniaxial tensile test, thus a flow curve was determined to describe the material behaviour. The initial temperatures of the environment, blank and tools were measured with an infrared thermal imager. A comprehensive finite element stress analysis of the deformable tools was carried out for the assembly phase of the dies, and for workpiece and tools in the deep drawing and ironing processes. The comparison of measured and numerically estimated temperatures had a good agreement, so the developed numerical model was confirmed and validated. This research study demonstrates how different process parameters can be investigated through a reliable and precise numerical model with complementary experimental research for the optimization of industrial technology.

## ARTICLE INFO

### Keywords:

Deep drawing;  
Tractrix die;  
Reinforcing rings;  
Finite element method (FEM);  
Experimental-numerical approach;  
Numerical modelling;  
Simulation;  
Infrared imaging technology;  
Simufact.forming

### \*Corresponding author:

[mandic@kg.ac.rs](mailto:mandic@kg.ac.rs)  
(Mandic, V.)

### Article history:

Received 28 December 2023

Revised 29 February 2024

Accepted 1 March 2024



Content from this work may be used under the terms of the Creative Commons Attribution 4.0 International License (CC BY 4.0). Any further distribution of this work must maintain attribution to the author(s) and the title of the work, journal citation and DOI.

## References

- [1] Park, G., Park, R., Kwak, H., Kim, C. (2021). Design of a combined redrawing-ironing process to manufacture a CNG pressure vessel liner, *Applied Sciences*, Vol. 11, No. 18, Article No. 8295, doi: [10.3390/app11188295](https://doi.org/10.3390/app11188295).
- [2] Pernis, R., Barényi, I., Kasala, J., Ličková, M. (2015). Evaluation of limiting drawing ration (LDR) in deep drawing process, *Acta Metallurgica Slovaca*, Vol. 21, No. 4, 258-268, doi: [10.12776/ams.v21i4.642](https://doi.org/10.12776/ams.v21i4.642).
- [3] Kesharwani, R.K., Basak, S., Panda, S.K., Pal, S.K. (2017). Improvement in limiting drawing ratio of aluminum tailored friction stir welded blanks using modified conical tractrix die, *Journal of Manufacturing Processes*, Vol. 28, Part 1, 137-155, doi: [10.1016/j.jmapro.2017.06.002](https://doi.org/10.1016/j.jmapro.2017.06.002).
- [4] Loganathan, C., Narayanasamy, R. (2005). Effect of mechanical properties on the wrinkling behaviour of three different commercially pure aluminium grades when drawn through conical and tractrix dies, *Materials Science and Engineering: A*, Vol. 406, No. 1-2, 229-253, doi: [10.1016/j.msea.2005.06.037](https://doi.org/10.1016/j.msea.2005.06.037).

- [5] Park, G.-Y., Kwak, H.-S., Jang, H.-S., Kim, C. (2022). Deep drawing process using a tractrix die for manufacturing liners for a CNG high-pressure vessel (Type II), *Chinese Journal of Mechanical Engineering*, Vol. 35, No. 15, 1-12, doi: [10.1186/s10033-022-00681-9](https://doi.org/10.1186/s10033-022-00681-9).
- [6] Reddy, A.C.S., Rajesham, S., Reddy, P.R. (2015). Experimental and simulation study on the warm deep drawing of AZ31 alloy, *Advances in Production Engineering & Management*, Vol. 10, No. 3, 153-161, doi: [10.14743/apem2015.3.199](https://doi.org/10.14743/apem2015.3.199).
- [7] Mandić, V. (2012). *Physical and numerical modelling of metal forming processes (in Serbian)*, Faculty of Mechanical Engineering, Kragujevac, Serbia.
- [8] Hrnjica, B., Behrem, Š. (2022), A new multi-objective optimization approach for process parameters optimization during numerical simulation of quenching steel parts, *Advances in Production Engineering & Management*, Vol. 17, No. 1, 16-32, doi: [10.14743/apem2022.1.418](https://doi.org/10.14743/apem2022.1.418).
- [9] Mandić, V., Čosić, P. (2011). Integrated product and process development in collaborative virtual engineering environment, *Tehnički Vjesnik – Technical Gazette*, Vol. 18, No. 3, 369-378.
- [10] Gusel, L., Boskovic, V., Domitner, J., Ficko, M., Brezocnik, M. (2018). Genetic programming method for modelling of cup height in deep drawing process, *Advances in Production Engineering & Management*, Vol. 13, No. 3, 358-365, doi: [10.14743/apem2018.3.296](https://doi.org/10.14743/apem2018.3.296).
- [11] Adamovic, D., Mandić, V., Jurkovic, Z., Grizelj, B., Stefanovic, M., Marinkovic, T., Aleksandrovic, S. (2010). An experimental modelling and numerical FE analysis of steel-strip ironing process, *Tehnički Vjesnik – Technical Gazette*, Vol. 17, No. 4, 435-444.
- [12] Elplacy, F., Samuel, M., Mostafa, R. (2022), Modelling and simulation of hot direct extrusion process for optimal product characteristics: Single and multi-response optimization approach, *Advances in Production Engineering & Management*, Vol. 17, No. 1, 33-44, doi: [10.14743/apem2022.1.419](https://doi.org/10.14743/apem2022.1.419).
- [13] Tomáš, M., Evin, E., Kepič, J., Hudák, J. (2019). Physical modelling and numerical simulation of the deep drawing process of a box-shaped product focused on material limits determination, *Metals*, Vol. 9, No. 10, 1058-1074, doi: [10.3390/met9101058](https://doi.org/10.3390/met9101058).
- [14] Volk, M., Nardin, B., Dolsak, B. (2014). Determining the optimal area-dependent blank holder forces in deep drawing using the response surface method, *Advances in Production Engineering & Management*, Vol. 9, No. 2, 71-82, doi: [10.14743/apem2014.2.177](https://doi.org/10.14743/apem2014.2.177).
- [15] Musafija, B. (1979). *Metal forming by plastic deformation*, Svetlost, Sarajevo, Bosnia and Herzegovina.
- [16] Romhanji, E., Milenković, V., Drobnjak, D. (1992). The grain size and alloying influence on the strain hardening of polycrystalline  $\alpha$ -brasses, *International Journal of Materials Research*, Vol. 83, No. 2, 110-114, doi: [10.1515/ijmr-1992-830208](https://doi.org/10.1515/ijmr-1992-830208).
- [17] Hexagon. HxGN virtual manufacturing, from <https://www.simufact.com/simufactforming-forming-simulation.html>, accessed November 25, 2023.
- [18] Popović, M., Mandić, V., Delić, M., Pavićević, V. (2021). Experimental-numerical analysis of hot forging process with monitoring of heat effects, In: Karabegović, I. (ed.), *New technologies, development and application IV, NT 2021, Lecture notes in networks and systems*, Springer, Cham, Switzerland, 341-349, doi: [10.1007/978-3-030-75275-0\\_38](https://doi.org/10.1007/978-3-030-75275-0_38).
- [19] Hou, F., Zhang, Y., Zhou, Y., Zhang, M., Lv, V., Wu, J. (2022). Review on infrared imaging technology, *Sustainability*, Vol. 14, No. 18, Article No. 11161, doi: [10.3390/su141811161](https://doi.org/10.3390/su141811161).
- [20] Usamentiaga, R., Venegas, P., Guerediaga, J., Vega, L., Molleda, J., Bulnes, F. (2014). Infrared thermography for temperature measurement and non-destructive testing, *Sensors*, Vol. 14, No. 7, 12305-12348, doi: [10.3390/s140712305](https://doi.org/10.3390/s140712305).
- [21] Fluke. Ti200, Ti300, Ti400, Thermal imagers, Users manual, from <https://www.fluke-direct.com/pdfs/cache/www.fluke-direct.com/ti200-60hz/manual/ti200-60hz-manual.pdf>, accessed December 15, 2023.